

NOTES:
1. TOLERANCE ±.015 UNLESS NOTED OTHERWISE.
2. TOP CONDUCTIVE LAYER TO BE .007' THICK POLYESTER WITH AN ANTI-GLARE COATING.
3. THE CONNECTOR IS LOCATED ON THE LEFT SIDE OF THE PANEL.
4. PIN ONE LOCATION IS THE TOP PIN WHEN VIEWING WITH CABLE TO THE LEFT.
5. PINOUT TO BE AS INDICATED.
FIN 1 - UPPER RIGHT.
PIN 3 - LOWER RIGHT.
PIN 3 - PLANE.
PIN 4 - UPPER LEFT.
6. TAIL TO BE TERMINATED USING AMP RECEPTACLE 2-487406-4 OR EQUIVALENT
7. HOUSING TO BE AMP PART NUMBER 487378-4 OR EQUIVALENT
8. TOTAL PANEL THICKNESS TO BE 0.087' NOMINAL.

CHKD: MLR
APVD: DIAGONAL 5 WIRE TOUCHSCREEN DATE: 12/10/07 | SCALE: 1:1 DATE: 12/14/07 | PART NUMBER: DATE: CANNON FALLS, MN 55009 SCALE: 1:1 MCTS TOL: ±,015 400399

REV INITIALS

DESCRIPTION